

Table of Contents

Media

Vacuum and linear materials

Ideal metals

Realistic metals

1111

Media

GSvit is based on use of a regular rectangular mesh, so we use e.g. 200x200x200 rectangular volume elements - voxels on which our problem is defined. Individual voxels in the computational domain can be filled with any material and there is no limitation on this, as discussed e.g. in sections on [basic geometries](#) and [tetrahedral meshes](#).

Internally, there are two basic ways how to assign the material properties to particular voxel:

- four 3D arrays representing local permittivity, permeability, electric and magnetic conductivity are used for completely general handling of a material, e.g. having a smooth gradient in the sample. This requires to have the arrays in memory, so for large computational domains it can be memory demanding
- one 3D integer array is used for materials definition, filled by material indices, while the material parameters itself are stored in a lookup table. This is suitable for small number of materials in the computational domain, however, also more complex materials, like metals, can be handled.

We can also combine both approaches - to load the local optical properties to the four arrays, but then to place some material set by lookup table over them.

Vacuum and linear materials

These are handled using either lookup table or detailed arrays, however in both cases the material is defined by relative permittivity, permeability, electrical conductivity and magnetic conductivity, right as these appear in the Maxwell's equations. So, for vacuum this set would be (1 1 0 0). When handling such material within the basic geometric entities Gwyddion surfaces or tetrahedral mesh input, you can enter them with material type identifier 0 in order to get the four fields filled. If a lookup table approach is used, these materials should have material type identifier 1.

Ideal metals

The only ideal metal model that we have now is a perfect electric conductor. This means that on the interface of such material the lateral electrical field components are zero. To enter such material, use tabulated values approach and set the material type identifier to 10.

Realistic metals

Special numerical models are usually used to treat the real metals, including their spectral properties within FDTD. Such approach is needed to handle properly the specific optical properties of metals. There are many different algorithms enabling us to parametrize the spectral dependence of optical properties of metal and use them in the calculation. These algorithms also hide the fact that the propagation of light through metal described only by its complex permittivity can't be handled easily via conventional grid spacing and time steps.

An example of calculated metal reflectivity via FDTD for different metals and algorithms is shown in

